



80040001



Bus coupling unit flush-mtd, ext. temp. sensor, KNX

Technical characteristics

Controls and indicators

Button / push-button with illuminated programming button

Connectivity

Interface as interface between KNX user module and bus line

Voltage

Operating voltage over bus 21...32 V DC

Electric current

Bus current consumption (data transfer) ≈ 10 mA

Dimensions

Insertion depth 32 mm

Width of rail mounted device (RMD) 0 modules

LED control

LED with red programming LED

Installation, mounting

Installation mode with spreader claws

Connection

Number of contacts 4

Bus connection bus connection via connecting terminal

Settings

Supported configuration modes system, easy

Equipment

Product type: product type: bus coupling unit

Buzzer/siren with integrated buzzer for acoustic identification of the device within the system

Use

Differentiation characteristic 3 - Sales external temperature sensor

Safety

REACH conform No

RoHS conform Yes

Halogen free No

Protection with dust protection flap for user interface (AST)

Use conditions

| | |
|-----------------------|------------|
| Operating temperature | -5...45 °C |
|-----------------------|------------|

| | |
|-------------------------------|--|
| Storage/transport temperature | -20...70 °C (storage at > 45°C reduces the service life) |
|-------------------------------|--|

| | |
|-------------|---|
| Temperature | additional connection for external temperature sensor |
|-------------|---|

Identification

| | |
|--------------------|--------------------|
| Application, usage | KNX - system units |
|--------------------|--------------------|

| | |
|----------------|-----------------------------------|
| Product family | product family: system components |
|----------------|-----------------------------------|

| | |
|------------------|-----|
| Main design line | KNX |
|------------------|-----|
