




80960329

**IP20**



**Cover for 2gang for push-button module, clearlenses, Q.x, p. white velvety**

**Technical characteristics**

**Architecture**

Fixing mode flush-mounting

**Functions**

operating concept "independent push-button" function predefined ; operating concept for "roller shutter/blind" function predefined ; switching of scenes (1..8) possible ; brightness value of the status LED for day/nighttime operation preset, change-over for day/nighttime operation possible ; integrated temperature sensor with output of the measured values ; Colour of status LED uniformly adjustable for complete device ; push-button functions: including switching, dimming, roller shutter/blind, timer, priority, operating mode changeover

Easy link functions

**Controls and indicators**

Button / push-button with programming button and red programming LED

**Voltage**

Operating voltage over bus 21...32 V DC

**Dimensions**

Height 58 mm

**Power**

Power consumption, KNX  $\approx$  108 mW

**Camera**

Lens with 2 clear lenses for the RGB status display of the push-button module

**Materials**

Colour of design line polar white

RAL colour RAL 9010 - Pure white

Material / workmanship lacquered

Material thermoplastic

Surface appearance velvety

Type of surface treatment Painted

**Connection**

Bus coupling unit with integral bus coupling unit

Bus connection bus connection via connecting terminal

**Settings**

**Use**

|  |                 |
|--|-----------------|
| Differentiation characteristic 2 - Sales | with clear lens |
|--|-----------------|

**Safety**

|                     |                             |
|---------------------|-----------------------------|
| Protection index IP | IP20                        |
| REACH conform       | Yes                         |
| RoHS conform        | Yes                         |
| Halogen free        | No                          |
| Protection          | with dismantling protection |

**Use conditions**

|                               |  |
|-------------------------------|--|
| Operating temperature         | -5...45 °C   |
| Storage/transport temperature | -20...70 °C (storage at > 45°C reduces the service life) |

**Identification**

|                          |   |
|--------------------------|---|
| Application, usage       | KNX - operating systems                             |
| Product family           | product family: push-button                         |
| Main design line         | KNX - Berker Q.1/Q.3                                |
| Secondary design line(s) | KNX, Berker Q.1, Berker Q.3, Berker Q.7, Berker Q.9 |