Technical characteristics	
Controls and indicators	
Operation	with 2-push-buttons operation concep
Main electrical features	
Nominal voltage	12
Voltage	
Operating voltage	via inse
Materials	
Colour of design line	polar whit
Equipment	
Brightness	
Brightness Safety	
	power failure proof, storabl
Safety	switch-on brightness level for use on dimmer inser power failure proof, storabl Ye
Safety REACH conform	power failure proof, storabl
Safety REACH conform RoHS conform	power failure proof, storabl Ye Ye
Safety REACH conform RoHS conform Halogen free	power failure proof, storabl Ye Ye
Safety REACH conform RoHS conform Halogen free Protection	power failure proof, storabl Ye Ye
Safety REACH conform RoHS conform Halogen free Protection Use conditions	power failure proof, storabl Ye Ye N with dismantling protectio -545 °
Safety REACH conform RoHS conform Halogen free Protection Use conditions Operating temperature	power failure proof, storabl Ye Ye N with dismantling protectio
Safety REACH conform RoHS conform Halogen free Protection Use conditions Operating temperature Energy-saving	power failure proof, storable Ye N with dismantling protectio -545 ° low intrinsic energy requiremen
Safety REACH conform RoHS conform Halogen free Protection Use conditions Operating temperature Energy-saving Relative humidity (without condensation)	power failure proof, storabl Ye Ye N with dismantling protectio -545 ° low intrinsic energy requiremen

Secondary design line(s)

tronics platform ; Berker S.1 ; Berker B.3 ; Berker B.7

\$**5**141189