


85648185



IP20

**KNX radio button 4gang quicklink, S.1/B.3/B.7, ant., matt**

**Technical characteristics**

**Functions**

ETS additional functions: +6 scenes, 1 button control up/down, operating mode on/off, dimming value, brightness display, push-button, status display, forced control

ETS additional functions

Functions for the push-button operation areas up/down or left/right can be freely configured as receiver for controlling the connected load and as transmitter for remote control of a blind, for example ; reset function (to factory setting) ; Configurable transmission and/or reception behaviour

Function

Light scenes scene saving lockable

Quicklink functions quicklink functions: switching, dimming, blind, 2 scenes, time switching, NO contact push-button, memory

**Controls and indicators**

Operation operating areas configurable as one or two-area operation

Button / push-button with configuration and function button

**Connectivity**

Radio protocol KNX Radio

Receiver category 2

**Power**

Radio transmission power < 10 mW

**Materials**

Colour of design line anthracite

RAL colour RAL 7021 - Black grey

Material thermoplastic

Surface appearance matt

**LED control**

LED with configuration and function LEDs ; LED application module/insert compatibility display

**Connection**

Bus connection integration in the KNX radio/TP gateway, surface-mounted, into the KNX TP system

**Settings**

Programming toolless quicklink configuration using buttons and LED display

**Equipment**

Number of radio channels	4
Number of quicklink links	max. 20 transmitter/receiver
Transmitter duty cycle	1 %
Brightness	switch-on brightness level for each operating area on configuration with dimmer insert, power failure proof, storable
<b>Safety</b>	
Protection	with dismantling protection
<b>Use conditions</b>	
Operating temperature	-5...45 °C
Energy-saving	low intrinsic energy requirement
Relative humidity (without condensation)	0...65 % (without condensation)
<b>Identification</b>	
Application, usage	Light control ; KNX radio- operating systems
Main design line	Berker S.1/B.3/B.7
Secondary design line(s)	Electronics platform ; Berker S.1 ; Berker B.3 ; Berker B.7
<b>Instructions</b>	
Information text	Extended operating options on 1gang inserts through 2 additional, freely-configurable radio channels.