



85648188



IP20

quicklink

KNX radio button 4gang quicklink, S.1/B.3/B.7, p. white, matt, plastic

Technical characteristics

Functions

ETS additional functions: +6 scenes, 1 button control up/down, operating mode on/off, dimming value, brightness display, push-button, status display, forced control

ETS additional functions

Functions for the push-button operation areas up/down or left/right can be freely configured as receiver for controlling the connected load and as transmitter for remote control of a blind, for example ; reset function (to factory setting) ; Configurable transmission and/or reception behaviour

Function

Light scenes scene saving lockable

Quicklink functions quicklink functions: switching, dimming, blind, 2 scenes, time switching, NO contact push-button, memory

Controls and indicators

Operation operating areas configurable as one or two-area operation

Button / push-button with configuration and function button

Connectivity

Radio protocol KNX Radio

Receiver category 2

Power

Radio transmission power < 10 mW

Materials

Colour of design line polar white

RAL colour RAL 9010 - Pure white

Surface appearance matt

LED control

LED with configuration and function LEDs ; LED application module/insert compatibility display

Connection

Bus connection integration in the KNX radio/TP gateway, surface-mounted, into the KNX TP system

Settings

Programming toolless quicklink configuration using buttons and LED display

Equipment

Number of radio channels 4

Number of quicklink links	max. 20 transmitter/receiver
Transmitter duty cycle	1 %
Brightness	switch-on brightness level for each operating area on configuration with dimmer insert, power failure proof, storable
Safety	
REACH conform	No
RoHS conform	Yes
Halogen free	No
Protection	with dismantling protection
Use conditions	
Operating temperature	-5...45 °C
Energy-saving	low intrinsic energy requirement
Relative humidity (without condensation)	0...65 % (without condensation)
Identification	
Application, usage	Light control ; KNX radio- operating systems
Main design line	Berker S.1/B.3/B.7
Secondary design line(s)	Electronics platform ; Berker S.1 ; Berker B.3 ; Berker B.7
Instructions	
Information text	Extended operating options on 1gang inserts through 2 additional, freely-configurable radio channels.