



HAB302

Load break switch 3P 20A

Technical characteristics

Architecture

| | |
|-----------------|------------------|
| Type of order | Short thumb-grip |
| Number of poles | 3 P |
| Type of pole | 3 P |
| Type of case | Fixed built-in |

Functions

| | |
|------------------|----|
| Reversing switch | No |
|------------------|----|

Configuration

| | |
|-------------------|------|
| Number of modules | 2.57 |
|-------------------|------|

Controls and indicators

| | |
|------------------------|----|
| Motor drive integrated | No |
|------------------------|----|

Main electrical features

| | |
|------------------------------|-------------|
| Rated operational voltage Ue | 380 / 415 V |
| Frequency | 50 Hz |

Voltage

| | |
|---------------------------------|--------|
| Rated insulation voltage | 800 V |
| Rated impulse withstand voltage | 8000 V |

Electric current

| | |
|--|---------|
| Rated operational current in AC21category B | 20 A |
| Rated current | 20 A |
| Short-circuit current with gI-gG fuses | 50 kA |
| Rated short-time withstand current 1s | 1.26 kA |
| Acceptable current rating with AC22 category B | 20 A |
| Rated operational current in AC23 category A | 20 A |
| Acceptable current rating with AC23 category B | 20 A |

Power

| | |
|---------------------------------------|-------|
| Total power loss under I _N | 0.8 W |
| Power loss per pole at I _N | 0.3 W |
| Contact rating with 400 V in AC1 | 13 kW |

Cover, door

| | |
|---------------|-----|
| Interlockable | Yes |
|---------------|-----|

Installation, mounting

| | |
|-------------------|------------|
| Tightening torque | 2 - 2.2 Nm |
|-------------------|------------|

Connection

| | |
|------------------------------------|-------------------|
| Connection cross-sect. rigid cable | 16mm ² |
|------------------------------------|-------------------|

| | |
|--------------------|------------|
| Type of connection | with screw |
|--------------------|------------|

Equipment

| | |
|---|---|
| Number of auxiliary contacts as normally closed contact | 0 |
|---|---|

| | |
|---|---|
| Number of auxiliary contacts as normally open contact | 0 |
|---|---|

| | |
|---|---|
| Number of auxiliary contacts as change-over contact | 0 |
|---|---|

| | |
|----------------------|----|
| Motor drive optional | No |
|----------------------|----|

Standards

| | |
|---------------|-------------|
| Standard text | IEC 60947-3 |
|---------------|-------------|

Safety

| | |
|---------------|-----|
| REACH conform | Yes |
|---------------|-----|

| | |
|--------------|-----|
| RoHS conform | Yes |
|--------------|-----|

| | |
|--------------|----|
| Halogen free | No |
|--------------|----|

Use conditions

| | |
|-----------------------|-------------|
| Operating temperature | -20...70 °C |
|-----------------------|-------------|