



RED612X



**IP20**

**Distributor/branch 2 ways RMD 2-wires**

**Technical characteristics**

**Functions**

|                  |                              |
|------------------|------------------------------|
| Function         | distributing                 |
| System functions | distribution of single lines |

**Dimensions**

|                                    |           |
|------------------------------------|-----------|
| Width of rail mounted device (RMD) | 1 modules |
|------------------------------------|-----------|

**Attenuation**

|                          |      |
|--------------------------|------|
| Distribution attenuation | 3 dB |
|--------------------------|------|

**Installation, mounting**

|                   |                         |
|-------------------|-------------------------|
| Mounting type     | din-Rail                |
| Installation mode | Rail mounted unit (RMD) |

**Connection**

|                |   |
|----------------|---|
| Bus connection | 2-wire, for video door stations ; 2-wire, for video indoor stations |
|----------------|---|

**Cable**

|             |              |
|-------------|--------------|
| Conductor Ø | 0.5...0.8 mm |
|-------------|--------------|

**Use**

|                    |   |
|--------------------|---|
| System technology  | 2-wire  |
| Video distribution | for distributing the incoming bus cable to the outgoing one ; for coupling the incoming bus cables to the outgoing ones ; unwired terminals must be completed with terminator |

**Software**

|                  |       |
|------------------|-------|
| Software version | V1000 |
|------------------|-------|

**Safety**

|               |     |
|---------------|-----|
| REACH conform | Yes |
| RoHS conform  | Yes |
| Halogen free  | No  |

**Use conditions**

|  |             |
|--|-------------|
| Operating temperature                    | 5...40 °C   |
| Storage/transport temperature            | -20...60 °C |
| Relative humidity (without condensation) | 0...65 %    |

**Identification**

|                  |               |
|------------------|---------------|
| Main design line | T electronics |
|------------------|---------------|