



RED621X



Distributor/branch 1 way flush-mounted 2-wire

Technical characteristics

Architecture

| | |
|-------------|----------------|
| Fixing mode | flush-mounting |
|-------------|----------------|

Functions

| | |
|------------------|-------------------------|
| Function | distributing |
| System functions | branches of a stub line |

Attenuation

| | |
|--------------------------|-------|
| Transmission loss | 1 dB |
| Distribution attenuation | 12 dB |

Materials

| | |
|--------|-------|
| Colour | black |
|--------|-------|

Installation, mounting

| | |
|---------------|---------------|
| Mounting type | flush-mounted |
|---------------|---------------|

Cable

| | |
|-------------|--------------|
| Conductor Ø | 0.5...0.8 mm |
|-------------|--------------|

Use

| | |
|--------------------|---|
| System technology | 2-wire |
| Video distribution | for branching off the bus cable from the continuous bus cable ; unwired terminals must be completed with terminator |

Software

| | |
|------------------|-------|
| Software version | V1000 |
|------------------|-------|

Safety

| | |
|--------------|----|
| Halogen free | No |
|--------------|----|

Use conditions

| | |
|--|-------------|
| Operating temperature | 5...40 °C |
| Storage/transport temperature | -20...60 °C |
| Relative humidity (without condensation) | 0...65 % |