



TJA450

**domovea Softwarelösung (Server + Client) mit USB/KNX Interface**

**Technical characteristics**

**Architecture**

Fixing mode REG

**Configuration**

Number of modules 6

**Controls and indicators**

Indicator lamp yes

Manual selection switches / push-buttons Selection switch for online/offline mode

**Connectivity**

IP KNX server to supply up to 30 visualisation clients simultaneously with KNX data

**Voltage**

Auxiliary voltage 24 V DC

Operating voltage over bus 21...32 V DC

**Electric current**

Current consumption (operation) ≈ 150 mA

**Dimensions**

Width of rail mounted device (RMD) 6 modules

**Power**

Power consumption (operation) 1.5 W

Total power loss under IN 3.9 W

**Storage**

RAM 128 MB

Memory allocated to the icons/wallpapers 20 MB

Graphics memory ≈ 20 MB

**Materials**

Colour stone grey

RAL colour RAL 7035 - Light grey

Material other

Material plastic

Type of surface treatment untreated

**Connection**

Number of IP cameras 10

Bus coupling unit	with integral bus coupling unit
Bus connection	bus connection via connecting terminal
Type of connection	Quickconnect
<b>Settings</b>	
Supported configuration modes	system
<b>Scope of delivery</b>	
Bus connection included	Yes
<b>Accessories included</b>	
Accessory for Android application	Yes
Accessory for IOS application	yes
<b>Equipment</b>	
Number of group	100
Number of controllable outputs	500
Number of clients	30
Number of energie measurement archives	100
Number of sequences	50
Number of USB interfaces	3
Processor	400 MHz
With configuration software	Yes
<b>Software</b>	
Client software	Yes
<b>Safety</b>	
Protection index IP	IP20
<b>Use conditions</b>	
Operating temperature	0...45 °C
<b>Identification</b>	
Main design line	KNX
<b>Instructions</b>	
Information text	Network technology skills are required for commissioning. System requirements: Windows XP, VISTA, Windows 7, Windows 8, Windows 10 (32 or 64-bit).