



WDI161



Touch Panel 16", Windows

Technical characteristics

Architecture

Fixing mode	flush-mounting
-------------	----------------

Functions

Touch function	Yes
Function	Disabling function for cleaning the user interface

Connectivity

Connection	RJ45 cable in scope of delivery
------------	---------------------------------

Voltage

Auxiliary voltage	24 V DC
-------------------	---------

Dimensions

Assembling height	11 mm
-------------------	-------

Screen

TFT screen size	16 "
Display	yes

Storage

RAM	2 GB
-----	------

Materials

RAL colour	RAL 7016 - Anthracite grey
Material	glass
Material family	Glass

Installation, mounting

Installation mode	for flush-mounted and hollow-wall mounting, for vertical and horizontal mounting
-------------------	--

Connection

Conductor cross-section (flexible), with wire end sleeve	0.75 mm²
--	----------

Settings

Supported configuration modes	system
-------------------------------	--------

Equipment

Text field	No
Light intensity	220 cd/m²
Processor	2 x 1 GHz

**Safety**

Protection index IP	IP20
---------------------	------

**Use conditions**

Operating temperature	5...35 °C
Storage/transport temperature	-20...60 °C
Relative humidity (without condensation)	10...90 %

**Identification**

Composition	Control element
Main design line	KNX