



WDW161

IP20

**Flush-mounted housing for WDI16x, flush with wall**

**Technical characteristics**

**Functions**

Touch function	No
Function	with Push-to-open mechanism for comfortable mounting

**Controls and indicators**

Operation	depending on the software visualisation one and two surface operation, stepless configuration based on sliding and page scrolling by swiping are supported
-----------	--

**Connectivity**

Connection	RJ45 cable in scope of delivery
Connectors / jacks	with USB/Mini USB type A adapter cable ; with RJ45 connector kit from connector and patch cable

**Dimensions**

Cavity wall opening (W x H x D)	387 x 242 x 74 mm
---------------------------------	-------------------

**Power**

Total power loss under IN	0 W
Dissipated energy in cable	0 W

**Screen**

Display	no
---------	----

**Materials**

Material family	Metal
-----------------	-------

**Installation, mounting**

Installation mode	for flush-mounted and hollow-wall mounting ; for vertical and horizontal mounting
-------------------	---

**Scope of delivery**

Component	Microphone and loudspeaker with echo suppression
-----------	--

**Equipment**

Interface type	other
Text field	No
Lighting	Display illumination can be switched on automatically using brightness sensor
low noise	silent, long-lasting convection cooling without fan

**Safety**

REACH conform	Yes
---------------	-----

RoHS conform	Yes
Halogen free	Yes
Protection	with cleaning cover

---

**Use conditions**

Storage/transport temperature	-20...60 °C
Relative humidity (without condensation)	10...90 %

---

**Identification**

Composition	other
Main design line	KNX