



WUZ672

**kallystx Ceiling loudspeaker 2"**

**Technical characteristics**

**Functions**

Loudness control No

**Main electrical features**

Frequency 120-20000 Hz

**Dimensions**

Insertion depth 35 mm

Depth of installed product 29 mm

Internal depth 29 mm

Installation opening Ø 68 mm

Recommended installation height 2.4...4 m

Installation wall thickness 15 mm

Loudspeaker chassis Ø 51 mm

**Frequency**

Frequency range audio 200 Hz...16 kHz

Frequency band 200 / 16000 Hz

Frequency response (-3 dB) 200...16000 Hz

**Power**

Nominal/music power handling 3/4 W

**Resistance**

Impedance 20 Ω

**Detection**

- at 1 kHz 180 °

- at 4 kHz 120 °

- at 8 kHz 140 °

**Materials**

Colour white

**Installation, mounting**

Built-in Yes

Mounting Method Surface

Installation mode with spring mechanism for ceiling installation

**Connection**

Conductor cross-section (flexible) max. 1.5 mm<sup>2</sup>

**Equipment**

---

|                                     |       |
|-------------------------------------|-------|
| Sound pressure level 1 W/1 m        | 82 dB |
| Sound pressure level at rated power | 87 dB |

**Standards**

---

|           |    |
|-----------|----|
| Approvals | CE |
|-----------|----|

**Identification**

---

|                  |                          |
|------------------|--------------------------|
| Main design line | Communication technology |
|------------------|--------------------------|

**Instructions**

---

|                  |   |
|------------------|---|
| Information text | Housing screws made of stainless steel. |
|------------------|---|