



ADM410T

RCBO 4P 6kA C-10A 30mA A

Technical properties

Electric current

Rated current	10 A
Rated residual operating current I _{dn}	30 mA
Rated current -25°C	12,30 A
Rated current at -20°C	12,10 A
Rated current -15°C	11,90 A
Rated current -10°C	11,70 A
Rated current -5°C	11,50 A
Rated current at 0°C	11,30 A
Rated current 5°C	11,10 A
Rated current 10°C	10,90 A
Rated current 15°C	10,70 A
Rated current at 20°C	10,50 A
Rated current 25°C	10,20 A
Rated current 30°C	10 A
Rated current 35°C	9,80 A
Rated current at 40°C	9,50 A
Rated current at 45°C	9,20 A
Rated current at 50°C	9 A
Rated current 55°C	8,70 A
Rated current 60°C	8,40 A
Rated short-circuit breaking capacity I _{cn} under 230 V AC according to IEC 61009-1	6 kA

Architecture

Curve	C
Neutral position	Right
Type of pole	4P
Number of protected poles	4

Capacity

Number of modules	4
-------------------	---

Safety

Residual current type	A
Ingress Protection (IP) class	IP2X

Voltage

Type voltage supply	AC
---------------------	----

Rated operational voltage Ue	230 - 415 V
Rated insulation voltage Ui	500 V
Dielectric strength value of power frequency	2 kV
Rated impulse withstand voltage Uimp	4000 V
Overvoltage category according to IEC 60947-1	3

Installation, mounting

Nominal tightening torque top terminal	2 - 2 Nm
Nominal tightening torque down terminal	2 - 2 Nm
Nominal tightening torque	2 - 2 Nm
360° mounting position possible	Yes
Type of top connection for modular devices	Screw terminal
Type of bottom connection for modular devices	biconnect, Bypass

Main electrical attributes

Rated short-circuit breaking capacity Icn AC according to IEC 60898-1	6 kA
---	------

Frequency

Frequency	50 - 50 Hz
-----------	------------

Connection

Cross-section of input with screws, for flexible conductors	1 - 16 mm²
Cross-section of input with screws, for massive conductors	1 - 25 mm²

Use conditions

Class of energy limitation I²t	3
Operating temperature	-25 - 40 °C

Dimensions

Height	84 mm
Width	71 mm
Depth	70 mm

Power

Total power loss under IN	9,70 W
---------------------------	--------