



CZ001

Auxiliary contact for RCCB 2(1C+1O) 6A 240V AC

Technical properties

Architecture

Fixing mode	Clipped
-------------	---------

Configuration

Number of modules	1
-------------------	---

Main electrical features

Rated operational voltage Ue	230 / 440 V
Frequency	50 Hz

Voltage

Rated insulation voltage	500 V
Rated operational voltage in DC	12 / 250 V

Electric current

Acceptable current rating with AC1	6 A
Rated current	6 A
I _{min} = f (U = 230 V AC)	6 A
I _{min} = f (U = 230 V DC)	0.6 A
I _{min} =f(U=400V AC) for power circuit	3 A

Dimensions

Width of installed product	18 mm
----------------------------	-------

Power

Total power loss under I _N	0.1 W
---------------------------------------	-------

Endurance

Electric endurance in number of cycles	6000
Number of mechanical operations	12000

Installation, mounting

Factory fitted	No
----------------	----

Equipment

Quantity of NC contacts	1
Quantity of NO contacts	1
Quantity of INV contacts	0

Standards

European directive WEEE	concerned
-------------------------	-----------

Safety

Halogen free	No
--------------	----

Use conditions

Operating temperature	-25...60 °C
Storage/transport temperature	-40...80 °C