




EE702



IP55

Compact twilight switch enhanced 16A

Technical properties

Main electrical features

Rated operational voltage Ue	230 V
Frequency	50/60 Hz

Voltage

Operating voltage	230 V~ +10%/-15%
-------------------	------------------

Electric current

Acceptable current rating with AC1	16 A
------------------------------------	------

Dimensions

Depth of installed product	42.5 mm
Height of installed product	95 mm
Length	80 mm
Width of installed product	42.5 mm

Power

Conventional transformers	1500 VA
Electronic transformers	1500 W

Power supply

Supply voltage	230 V
----------------	-------

Materials

RAL colour	RAL 9010 - Pure white
------------	-----------------------

Lighting control

Brightness measurement range	2 / 1000 Lux
Fluorescent lamps with electronic ballast (EB)	16 x 58 W

Fluorescent bulbs control

Compact fluorescent lamps	20 x 20 W
Fluorescent lamps uncompensated	2000 W

Incandescent bulbs control

Max. power with incandescent lamps	2300 W
230 V incandescent lamps and halogen lamps	2300 W

Installation, mounting

Mounting type	surface-mounted
---------------	-----------------

for wall and mast assembly ; with pipe clamp for
mast fixing ; Installation possible on flush-mounted
box

Installation mode

Connection

Connection cross-sect. flexible conductor	1 / 4mm ²
Connection cross-sect. rigid cable	1 / 4mm ²
Conductor cross-section	1...4 mm ²
Number of contacts	1
Type of contacts	1NO
Type of connection	with screw terminals

Settings

Delay ON	10 s
Delay OFF	40 s

Setting
Brightness continuously adjustable on insert via
potentiometer ; Switch-on/switch-off delay
continuously adjustable via potentiometer

Equipment

Brightness On/off brightness value individually adjustable

Safety

REACH conform	Yes
RoHS conform	Yes

Use conditions

Storage/transport temperature -30...60 °C

Identification

Main design line House electronics