




EE860



## Motion detector comfort 220°, IP55, wall mounted, blanc

### Technical properties

#### Architecture

Bus system Without

#### Functions

Function Presence simulation ; can be used as a single unit, main device or extension unit

#### Main electrical features

Frequency 50/60 Hz

#### Dimensions

Height of installed product 2.5 m

Recommended installation height 2.5 m

#### Reach distance

Range, side each ≈ 8 m

#### Power supply

Supply voltage 230 V +10% / -15%

#### Detection

Detection angle 220 °

Detection angle 220 °

Frontal detecting distance 16 m

Side detecting distance 10 m

#### Materials

Colour white

RAL colour RAL 9010 - Pure white

Material plastic

#### Lighting control

Response brightness, adjustable ≈ 5...1000 lx

Brightness measurement range 5 / 1000 Lux

#### LED control

230V LED lamps 20 x 20 W

LED with LED detection and mode indicator

#### Installation, mounting

Installation mode for wall and ceiling mounting, corner installation with adapter

**Connection**

---

Type of connection	with screw terminals
--------------------	----------------------

---

**Settings**

---

Response value sensitivity adjustable	Yes
---------------------------------------	-----

---

Delay time, adjustable	5 s...30 mn
------------------------	-------------

---

Setting	with potentiometers for setting the response brightness and delay time without dismantling
---------	--

**Scope of delivery**

---

Component	with fitting material
-----------	-----------------------

---

**Equipment**

---

Remote controllable	EE806
---------------------	-------

---

Angle of horizontal detection	220 °
-------------------------------	-------

---

Slewing	vertically slewing and horizontally rotating
---------	--

**Safety**

---

REACH conform	Yes
---------------	-----

---

RoHS conform	Yes
--------------	-----

**Use conditions**

---

Operating temperature	-20...55 °C
-----------------------	-------------

---

Storage/transport temperature	-20...60 °C
-------------------------------	-------------

---

Energy-saving	low intrinsic energy requirement ; energy saving by means of presence and brightness-dependent ON and OFF switching of light
---------------	--

**Identification**

---

Application, usage	Motion detector
--------------------	-----------------

---

Main design line	Motion detectors
------------------	------------------