




EE870



IP55

Motion detector comfort 220/360°, IP55, wall mounted, white

Technical properties

Architecture

Fixing mode surface-mounting

Main electrical features

Frequency 50/60 Hz

Voltage

Operating voltage 230 V~ +10%/-15%

Dimensions

Height of installed product 2.5 m

Recommended installation height 2.5 m

Power

Power consumption (standby) ≈ 1.2 W

Incandescent bulb power 2300 W

Measurement

Detection field, semi-circular shaped ≈ 10 x 20 m

Detection

Detection angle 220 / 360 °

Detection angle 220 °

Detection field Ø, on floor ≈ 6 m

Materials

Colour white

Lighting control

Response brightness, adjustable ≈ 5...1000 lx

Brightness measurement range 5 / 1000 Lux

Fluorescent lamps with electronical ballast (EB) 580 W

Fluorescent bulbs control

Energy-saving lamps 20 x 20 W

Fluorescent lamps parallel compensated 400 W / 47 µF

Incandescent bulbs control

12 V halogen lamps 1500 W

230 V incandescent lamps and halogen lamps 2300 W

Installation, mounting

Maximum Mounting Height	2.5 m
-------------------------	-------

Connection

Type of connection	with screw terminals
--------------------	----------------------

Cable

Wire	with cable entry
------	------------------

Settings

Response value sensitivity adjustable	Yes
---------------------------------------	-----

Response sensitivity, settable	20...100 %
--------------------------------	------------

Delay time, adjustable	5 s...30 mn
------------------------	-------------

Setting	with potentiometers for fine adjustment of the response brightness, sensitivity and delay time
---------	--

Scope of delivery

Component	with fitting material
-----------	-----------------------

Equipment

Potential-free	with potential-free contact
----------------	-----------------------------

Slewing	vertically slewing and horizontally rotating
---------	--

Safety

Protection index IP	IP55
---------------------	------

Protection class	isol.class II
------------------	---------------

Use conditions

Operating temperature	-20...55 °C
-----------------------	-------------

Storage/transport temperature	-20...60 °C
-------------------------------	-------------

Identification

Application, usage	Motion detector
--------------------	-----------------

Main design line	Motion detectors
------------------	------------------