



EG103E



Digital time switch weekly 1 channel Evolution

Technical properties

Functions

Number of function channels	1
Function	Presence simulation ; Keylock by means of blocking key ; with pulse function

Configuration

Switch mode	change-over contact
Number of modules	2

Controls and indicators

Indication / display	LC display with illumination
----------------------	------------------------------

Main electrical features

Rated operational voltage Ue	195 / 230 / 264 V
Frequency	50 Hz

Voltage

Operating voltage	230 V~
-------------------	--------

Dimensions

Depth of installed product	64 mm
Height of installed product	85 mm
Length	85 mm
Width of installed product	35 mm
Width of rail mounted device (RMD)	2 modules

Power

Power consumed	6 VA
Total power loss under IN	2 W
Loss power at full load	≈ 2 W
Power dissipation per coil	0.5 W

Measurement

Running accuracy	± 1.5 s/day
------------------	-------------

Battery

Power reserve [years]	≈ 5 a
Battery / storage battery	with lithium battery type: 1/2 LR06

Incandescent bulbs control

Max. power with incandescent lamps	2300 W
------------------------------------	--------

Installation, mounting

Installation mode	for mounting on DIN rail
-------------------	--------------------------

Connection

Connection cross-sect. flexible conductor	1 / 6mm ²
Connection cross-sect. rigid cable	1,5 / 10mm ²
Conductor cross-section (flexible)	1...6 mm ²
Conductor cross-section (rigid)	1.5...10 mm ²
Number of contacts	1
Type of contacts	1 changeover
Type of connection	with screw terminals
Contact	with potential-free switching contact

Settings

Number of program steps	56
Summer / Winter time change	automatic
Shortest switching time	1 mn
Type of programming	digital
Program cycles	Programme cycles: 1 x 7 days
Programming cycle	1X7D.
Programs	with random programme ; holiday programme with date activation
Programming	Programming possible without mains voltage
Time	with automatic summer/winter time change-over

Equipment

Number of channels	1
Number of switching times for on/off	56
Supply failure reserve	5 years
With holidays program	Yes

Use

Cycle	weekly
-------	--------

Safety

Key	with programming key
-----	----------------------

Use conditions

Operating temperature	-5...45 °C
Working accuracy	1,5
Storage/transport temperature	-20...70 °C