



FU72DN

Enclosure, NewVegaD, 1287x55	0v150mm 169 module	as flush-mounted distribution

Technical properties

	nfig			
LO	ntic	lura	ITIC	ın

Module	with terminals
Number of modules	168

Electric current

Rated current	160 A

Dimensions

Insertion depth	110 mm
Depth of installed product	150 mm
Internal depth	110 mm
Height of installed product	1287 mm
Installation height	1287 mm
Width of installed product	600 mm
Width in division units	24
Thickness of sidewall material	1 mm
Built-in width	550 mm

Cover, door

Cover type	With Notch
Door locking	without
Door leave	single
Cover type	none / closed
Transparent cover or door	No

Materials

Colour	white	
RAL colour	RAL 9010 - Pure white	
Type of surface treatment	powder-coated	

Installation, mounting

Suitable for outdoor use	No

Connection

Settings

Enclosure type	Distributor empty cabinet

Equipment

Number of rows	7
Nullibel of fows	,

Quantity of section in width	2
Quantity of rails	7
Can be accessorized	Yes
Number of openings for flange plates	2
Extension possible	No
Earthing terminal block	No
Neutral terminal block	No
Signal passing door	No
Standards	
European directive WEEE	not concerned
Safety	
IK protection code against mecanical impacts	IK07
Protection class	isol.class II
REACH conform	No
RoHS conform	Yes
Halogen free	No