



HMT200DR

**Moulded Case Circuit Breaker h3+ P250 TM ADJ 3P3D 200A 50kA FTC**

**Technical properties**

**Electric current**

Rated current	200 A
Rated ultimate short-circuit breaking capacity Icu under 400 V AC IEC 60947-2	50 kA
Rated ultimate short-circuit breaking capacity Icu under 240 V AC IEC 60947-2	65 kA
Rated service breaking capacity Ics under 230 V AC according to IEC 60947-2	65 kA
Rated service breaking capacity Ics under 400 V AC according to IEC 60947-2	50 kA

**Architecture**

Number of poles	3
Control/operation element	Toggle
Device construction type	Fixed built-in
Neutral position	Without neutral

**Frequency**

Frequency	50 - 60 Hz
-----------	------------

**Voltage**

Rated impulse withstand voltage Uimp	8000 V
Rated insulation voltage Ui	800 V
Rated operational voltage Ue	220 - 690 V

**Functions**

Trip unit	TM A/A
-----------	--------

**Power**

Total power loss under IN	36 W
---------------------------	------

**Endurance**

Electric endurance in number of cycles	10000
Number of mechanical operations	40000

**Safety**

Ingress Protection (IP) class	IP4X
-------------------------------	------

**Connection**

Cross-section flexible conductor	35 - 150 mm <sup>2</sup>
Cross-section rigid conductor	35 - 185 mm <sup>2</sup>

**Cover, door**

Interlockable

Yes

---

**Cable**

Cable material

Copper, Aluminium

---

**Compatibility**

Compatible with RDC AOB

No

Suitable for DIN Rail

No

Suitable for distribution board

Yes

---

**Dimensions**

Height

165 mm

Width

105 mm

Depth

97 mm

---

**Installation, mounting**

Mounting-/Connection Position

Front

Nominal tightening torque

12 - 12 Nm

---

**Electrical protection**

Instantaneous protection (Ii): dial setting  
coefficient

6, 8, 10, 12