



TG053A



Weather station KNX GPS

Technical properties

Awal	hita	
Arc	nite	cture

Type of product analogic multifunction

Functions

Function

Precipitation (Yes/No) 1 bit

Measuring of precipitation, temperature, wind, brightness; with 8 logical AND- and OR-logic functions

Controls and indicators

Control Facade control

Button / push-button with programming button

Connectivity

Signal output No

with logic gates for linking the limiting value results;
with blocking modules for filtering input objects

Inputs depending on blocking objects

Voltage

Auxiliary voltage 12...40 V AC/DC

Operating voltage over bus 21...32 V DC

Electric current

Rated current (heating incl.) 80 mA

Dimensions

Dimensions (LLxwwxhh) 77x96 x118mm

Measurement

Speed measurement range 0 / 35 m/s

Temperature measurement range -30 / 80 °C

Measuring range, wind speed 0...35 m/s

Measuring range, wind strengths 0...35 Bft

Detection

with wind, precipitation, twilight, temperature and Sensor brightness sensor

Lighting control

Brightness measurement range 0 / 150000 Lux

LED control

LED with red programming LED

Installation mode	for wall and mast assembly ; with pipe clamp for mast fixing
Connection	
Bus coupling unit	with integral bus coupling unit
Type of connection	with plug-in terminals for power supply
Bus connection	bus connection via connecting terminal
Settings	
Supported configuration modes	system
Setting	delay times and hysteresis adjustable
Time	with automatic summer/winter time change-over ; Calender timer ; Week timer
Equipment	
Number of binary inputs	0
Heating	with heater element for winter operation
Use	
Differentiation characteristic 3 - Sales	with integral bus coupling unit
Safety	
Protection index IP	IP44
REACH conform	Yes
RoHS conform	Yes
Use conditions	
Operating temperature	-3050 °C
temperatur	
Temperature measuring range, linear	-3080 °C
Identification	
Main design line	KNX
Instructions	

Ensure correct orientation and free-standing installation.

Information text