



TXM632C



OUTPUT DEVICE FOR 12 SHUTTERS / BLINDS 230V~ 4A / NE

Technical properties

Architecture

Bus system	KNX
Number of blinds/shutters outputs	12
Fixing mode	REG

Functions

Bus module detachable	No
Multi-phase mode	suitable to switch different external conductors

Configuration

Number of modules	10
-------------------	----

Controls and indicators

Indicator lamp	yes
Manual selection switches / push-buttons	6 manual operation buttons for up/down per channel/device

Main electrical features

Type of supply voltage	AC
Frequency	50/60 Hz
Rated current	4 A

Voltage

Auxiliary voltage	230...240 V AC
Operating voltage over bus	21...32 V DC
System supply voltage	30V DC via bus

Electric current

Bus current consumption (data transfer)	7 mA
Bus current consumption (idle)	5 mA
Number of entry circuits	0
Maximum switching current	4 A
Switching current at $\cos \varphi = 0.6$	max. 4 A

Dimensions

Width of rail mounted device (RMD)	10 modules
Height	90 mm

Power

Contact rating with 230 V in AC1	920 W
----------------------------------	-------

Materials

Colour	light grey
--------	------------

Connection

Conductor cross-section (flexible)	0.75...2.5 mm ²
------------------------------------	----------------------------

Conductor cross-section (rigid)	0.75...2.5 mm ²
---------------------------------	----------------------------

Bus coupling unit	with integral bus coupling unit
-------------------	---------------------------------

Type of connection	with screw terminals
--------------------	----------------------

Bus connection	bus connection via connecting terminal
----------------	--

Settings

Supported configuration modes	system
-------------------------------	--------

Scope of delivery

Bus connection included	Yes
-------------------------	-----

Equipment

Modular expandability	No
-----------------------	----

Safety

Protection index IP	IP20
---------------------	------

Use conditions

Operating temperature	-5...45 °C
-----------------------	------------

Storage/transport temperature	-20...70 °C
-------------------------------	-------------

Identification

Main design line	KNX
------------------	-----