

Yes



## ${\bf Door, golf, white, accessory, for\ VF/VS212}$

## **Technical properties**

Height of installed product 280 mm Width of installed product 280 mm Built-in height 375 mm Built-in width 280 mm Cover, door  Number of keylock of the door 0 Door leave single Transparent cover or door No  Materials  Colour white RAL colour RAL 9010 - Pure white Material plastic Surface appearance glossy Type of surface treatment untreated Installation, mounting  Suitable for outdoor use No Equipment Number of rows 2 Quantity of section in width 1 Standards European directive WEEE not concerned Safety  KF protection code against mecanical impacts isol.class II REACH conform Yes	Architecture	
Depth of installed product 16.5 mm Internal depth 16.5 mm Height of installed product 375 mm Width of installed product 280 mm Width of installed product 280 mm Built-in height 375 mm Built-in width 280 mm Built-in width 280 mm Cover, door Voor leave single Transparent cover or door No Materials Colour white RAL colour RAL 9010 - Pure white Material plastic Surface appearance glossy Type of surface treatment untreated Installation, mounting Suitable for outdoor use No Equipment Voor Standards Standards Surface appearance Transparent over or middle for outdoor use No Equipment Voor Standards Standard	Intended door position	left
Depth of installed product 16.5 mm Internal depth 16.5 mm Internal depth 16.5 mm Height of installed product 375 mm Width of installed product 280 mm Built-in height 375 mm Built-in width 280 mm Cover, door  Number of keylock of the door 0 Door leave single Transparent cover or door No  Materials  Colour white RAL colour RAL 9010 - Pure white Material plastic Surface appearance glossy Type of surface treatment untreated Installation, mounting Suitable for outdoor use No  Equipment Number of rows 2 Quantity of section in width 1  Standards  European directive WEEE not concerned Safety  IK protection code against mecanical impacts isol.class II REACH conform Yes	Fixing mode	Clamping
Internal depth 16.5 mm Height of installed product 375 mm Width of installed product 280 mm Width of installed product 280 mm Built-in height 375 mm Built-in width 280 mm Cover, door  Number of keylock of the door 0 Door leave single Transparent cover or door No  Materials  Colour white RAL colour RAL 9010 - Pure white Material plastic Surface appearance glossy Type of surface treatment untreated Installation, mounting Suitable for outdoor use No  Equipment Number of rows 2 Quantity of section in width 1  Standards European directive WEEE not concerned Safety  IK protection code against mecanical impacts isol.class. II REACH conform Yes	Dimensions	
Height of installed product 280 mm Width of installed product 280 mm Built-in height 375 mm Built-in width 280 mm Cover, door  Number of keylock of the door 0 Door leave single Transparent cover or door No  Materials  Colour white RAL colour RAL 9010 - Pure white Material plastic Surface appearance glossy Type of surface treatment untreated Installation, mounting Suitable for outdoor use No Equipment Number of rows 2 Quantity of section in width 1 Standards European directive WEEE not concerned Safety  K protection code against mecanical impacts isol.class II REACH conform Yes	Depth of installed product	16.5 mm
Width of installed product 280 mm Built-in height 375 mm Built-in width 280 mm  Cover, door  Number of keylock of the door 0 Door leave single Transparent cover or door No  Materials  Colour white RAL 2010ur RAL 9010 - Pure white Material plastic Surface appearance glossy Type of surface treatment untreated  Installation, mounting  Suitable for outdoor use No  Equipment  Number of rows 2 Quantity of section in width 1 Standards  European directive WEEE not concerned  Safety  K protection code against mecanical impacts isol.class II REACH conform Yes	Internal depth	16.5 mm
Built-in height 375 mm Built-in width 280 mm  Cover, door  Number of keylock of the door 0 Door leave single Transparent cover or door No  Materials  Colour white RAL colour RAL 9010 - Pure white Material plastic Surface appearance glossy Type of surface treatment untreated  Installation, mounting  Suitable for outdoor use No  Equipment Number of rows 2 Quantity of section in width 1  Standards  European directive WEEE not concerned  Safety  IK protection code against mecanical impacts isol.class II REACH conform Yes	Height of installed product	375 mm
Built-in width 280 mm  Cover, door  Number of keylock of the door 0  Door leave single Transparent cover or door No  Materials  Colour white RAL colour RAL 9010 - Pure white Material plastic Surface appearance glossy Type of surface treatment untreated  Installation, mounting  Suitable for outdoor use No  Equipment  Number of rows 2  Quantity of section in width 1  Standards  European directive WEEE not concerned  Safety  IK protection code against mecanical impacts inspacts isol.class II REACH conform Yes	Width of installed product	280 mm
Cover, door  Number of keylock of the door 0 Door leave single Transparent cover or door No  Materials  Colour white RAL colour RAL 9010 - Pure white Material plastic Surface appearance glossy Type of surface treatment untreated  Installation, mounting  Suitable for outdoor use No  Equipment  Number of rows 2 Quantity of section in width 1  Standards  European directive WEEE not concerned  Safety  IK protection code against mecanical impacts inspacts isol.class II REACH conform Yes	Built-in height	375 mm
Number of keylock of the door 0 Door leave single Transparent cover or door No  Materials  Colour White RAL colour RAL 9010 - Pure white Material plastic Surface appearance glossy Type of surface treatment untreated  Installation, mounting  Suitable for outdoor use No  Equipment  Number of rows 2 Quantity of section in width 1  Standards  European directive WEEE not concerned  Safety  Kr protection code against mecanical impacts isol.class II REACH conform Yes	Built-in width	280 mm
Door leave single Transparent cover or door No  Materials  Colour RAL 9010 - Pure white Material plastic Surface appearance glossy Type of surface treatment untreated  Installation, mounting  Suitable for outdoor use No  Equipment  Number of rows 2 Quantity of section in width 1  Standards  European directive WEEE not concerned  Safety  IK protection code against mecanical impacts IK07  Protection class II  REACH conform Yes	Cover, door	
Transparent cover or door No  Materials  Colour RAL 9010 - Pure white  Material plastic  Surface appearance glossy Type of surface treatment untreated  Installation, mounting  Suitable for outdoor use No  Equipment  Number of rows 2  Quantity of section in width 1  Standards  European directive WEEE not concerned  Safety  IK protection code against mecanical impacts IK07  Protection class II  REACH conform Yes	Number of keylock of the door	0
Materials  Colour white  RAL colour RAL 9010 - Pure white  Material plastic  Surface appearance glossy Type of surface treatment untreated  Installation, mounting  Suitable for outdoor use No  Equipment  Number of rows 2  Quantity of section in width 1  Standards  European directive WEEE not concerned  Safety  IK protection code against mecanical impacts IK07  Protection class isol.class II  REACH conform Yes	Door leave	single
Colour RAL 2010ur RAL 9010 - Pure white Material plastic Surface appearance glossy Type of surface treatment untreated  Installation, mounting Suitable for outdoor use No  Equipment Number of rows 2 Quantity of section in width 1  Standards European directive WEEE not concerned  Safety  IK protection code against mecanical impacts IK07 Protection class isol.class II REACH conform Yes	Transparent cover or door	No
RAL colour RAL 9010 - Pure white Material plastic Surface appearance glossy Type of surface treatment untreated Installation, mounting Suitable for outdoor use No Equipment Number of rows 2 Quantity of section in width 1  Standards European directive WEEE not concerned Safety  IK protection code against mecanical impacts IK07 Protection class isol.class II REACH conform Yes	Materials	
Material plastic Surface appearance glossy Type of surface treatment untreated  Installation, mounting Suitable for outdoor use No  Equipment Number of rows 2 Quantity of section in width 1  Standards European directive WEEE not concerned  Safety  IK protection code against mecanical impacts IK07 Protection class isol.class II REACH conform Yes	Colour	white
Surface appearance glossy Type of surface treatment untreated  Installation, mounting  Suitable for outdoor use No  Equipment  Number of rows 2  Quantity of section in width 1  Standards  European directive WEEE not concerned  Safety  IK protection code against mecanical impacts IK07  Protection class isol.class II  REACH conform Yes	RAL colour	RAL 9010 - Pure white
Type of surface treatment untreated  Installation, mounting  Suitable for outdoor use No  Equipment  Number of rows 2  Quantity of section in width 1  Standards  European directive WEEE not concerned  Safety  IK protection code against mecanical impacts IK07  Protection class isol.class II  REACH conform Yes	Material	plastic
Installation, mounting  Suitable for outdoor use No  Equipment  Number of rows 2  Quantity of section in width 1  Standards  European directive WEEE not concerned  Safety  IK protection code against mecanical impacts IK07  Protection class is isol.class II  REACH conform	Surface appearance	glossy
Suitable for outdoor use No  Equipment  Number of rows 2  Quantity of section in width 1  Standards  European directive WEEE not concerned  Safety  IK protection code against mecanical impacts IK07  Protection class isol.class II  REACH conform Yes	Type of surface treatment	untreated
Equipment  Number of rows 2  Quantity of section in width 1  Standards  European directive WEEE not concerned  Safety  IK protection code against mecanical impacts IK07  Protection class isol.class II  REACH conform Yes	Installation, mounting	
Number of rows 2  Quantity of section in width 1  Standards  European directive WEEE not concerned  Safety  IK protection code against mecanical impacts IK07  Protection class isol.class II  REACH conform Yes	Suitable for outdoor use	No
Quantity of section in width 1  Standards  European directive WEEE not concerned  Safety  IK protection code against mecanical impacts IK07  Protection class isol.class II  REACH conform Yes	Equipment	
Standards  European directive WEEE not concerned  Safety  IK protection code against mecanical impacts IK07  Protection class isol.class II  REACH conform Yes	Number of rows	2
European directive WEEE not concerned  Safety  IK protection code against mecanical impacts IK07  Protection class isol.class II  REACH conform Yes	Quantity of section in width	1
Safety  IK protection code against mecanical impacts  Protection class  IK07  REACH conform  Yes	Standards	
IK protection code against mecanical impacts  Protection class  REACH conform  IK07  Yes	European directive WEEE	not concerned
impactsIK07Protection classisol.class IIREACH conformYes	Safety	
REACH conform Yes		IK07
	Protection class	isol.class II
RoHS conform Yes	REACH conform	Yes
	RoHS conform	Yes

**Use conditions** 

Operating temperature -25...40 °C