

EE860

Motion detector comfort 220°, IP55, wall mounted, blanc



- Architecture
 - Fixing mode
surface-mounting
- Functions
 - Function
Presence simulation ; can be used as a single unit, main device or extension unit
- Main electrical features
 - Frequency
50;60 Hz
- Dimensions
 - Height of installed product
2.5 m
 - Dimensions (W x H x D)
91/139/153 mm
- Frequency
 - Frequency
50;60 Hz
- Power
 - Incandescent bulb power
2300 W
- Capacity
 - Breaking capacity
16A 250V AC1
- Cover, door
 - Cover
with cover elements to limit the detection field
- Power supply

- Supply voltage
230 V +10% ; -15%
- Detection
 - Side detecting distance
10 m
 - Detection angle
220 °
- Materials
 - Colour
white
- Lighting control
 - Brightness measurement range
5 / 1000 Lux
- Installation, mounting
 - Maximum Mounting Height
4 m
- Connection
 - Connection type
quick connect
 - Type of contacts
contact floating
 - Type of connection
with screw terminals
- Settings
 - Time delayed range
5s to 30 min
 - Setting
with potentiometers for setting the response brightness and delay time without dismantling
 - Response value sensitivity adjustable
Yes
- Scope of delivery
 - Component
with fitting material
- Equipment
 - Remote controllable
EE806
- Safety
 - Protection index IP
IP55
- Use conditions
 - Operating temperature
-20/55 °C
- Identification
 - Application, usage
Motion detector