



ACC125

RCBO Electronic 1M 1P 10kA C-25A 10mA AC Class

Technical characteristics

| Architecture | |
|------------------|------|
| Neutral position | righ |
| Number of poles | 1 |
| Type of pole | 1 |
| Curve | |

| Rated operational voltage Ue | 230 / 240 V |
|---------------------------------|-------------|
| Frequency | 50 Hz |
| Voltage | |
| Rated insulation voltage | 250 V |
| Max operating voltage | 253 V |
| Rated impulse withstand voltage | 4000 V |

| F | Rated residual operating current | 10 mA |
|---|---|-------|
| | Rated short circuit breaking capacity Icn under 230V AC according IEC60898-1 | 10 kA |

| Electric current / temperature | | |
|--------------------------------|------|--|
| Rating current 30°C | 25 A | |
| Dimensions | | |

| Depth of installed product | 73 mm |
|-----------------------------|---------|
| Height of installed product | 115 mm |
| Width of installed product | 17.8 mm |

| Power | |
|---------------------------|-------|
| Total power loss under IN | 6.9 W |

| Endurance | |
|--|------|
| Electric endurance in number of cycles | 2000 |
| Number of mechanical operations | 1000 |

| Installation, mounting | |
|------------------------|-------|
| Tightening torque | 2,1Nm |

| Standards | |
|-------------------------|--------------------------|
| Standard text | IEC 61009-1 ; EN 61009-1 |
| European directive WEEE | concerned |

| Sarety | |
|-----------------------|------|
| Protection index IP | IP20 |
| Residual current type | ΔC |