



RCBO Electronic 1M 1P 10kA C-45A 30mA A Class

Technical characteristics

	right
Neutral position Number of poles	1 P
Type of pole	1 P
Curve	С
Main electrical features	
Rated operational voltage Ue	230 / 240 V
Frequency	50 Hz
Voltage	
Rated insulation voltage	250 V
Max operating voltage	253 V
Rated impulse withstand voltage	4000 V
Electric current	
Rated residual operating current	30 mA
Rated short circuit breaking capacity Icn under 230V AC according IEC60898-1	10 kA
Electric current / temperature	
Rating current 30°C	45 A
Dimensions	
Dimensions Depth of installed product	70 mm
Depth of installed product	
Depth of installed product Height of installed product	110 mm
Depth of installed product Height of installed product Width of installed product	110 mm 17.8 mm
Depth of installed product Height of installed product Width of installed product Power	110 mm 17.8 mm
Depth of installed product Height of installed product Width of installed product Power Total power loss under IN	110 mm 17.8 mm 12.42 W
Depth of installed product Height of installed product Width of installed product Power Total power loss under IN Endurance	110 mm 17.8 mm 12.42 W
Depth of installed product Height of installed product Width of installed product Power Total power loss under IN Endurance Electric endurance in number of cycles	110 mm 17.8 mm 12.42 W
Depth of installed product Height of installed product Width of installed product Power Total power loss under IN Endurance Electric endurance in number of cycles Number of mechanical operations	110 mm 17.8 mm 12.42 W 2000 1000
Depth of installed product Height of installed product Width of installed product Power Total power loss under IN Endurance Electric endurance in number of cycles Number of mechanical operations Installation, mounting	110 mm
Depth of installed product Height of installed product Width of installed product Power Total power loss under IN Endurance Electric endurance in number of cycles Number of mechanical operations Installation, mounting Tightening torque	110 mm 17.8 mm 12.42 W 2000

Safety

Residual current type

Α