



BTC380E



## Earth leakage add-on-block 3P 125A Adjustable type AC

### Technical characteristics

#### Architecture

Neutral position	Left or right
Number of poles	3 P

#### Main electrical features

Rated operational voltage $U_e$	415 V
Frequency	50 Hz

#### Voltage

Rated insulation voltage	500 V
Rated impulse withstand voltage	6000 V

#### Electric current

Rated residual operating current	300 mA / 500 mA / 1 A
----------------------------------	-----------------------

#### Electric current / temperature

Rating current 30°C	125 A
---------------------	-------

#### Dimensions

Depth of installed product	69 mm
Height of installed product	103 mm
Width of installed product	187 mm

#### Power

Total power loss under IN	11.25 W
---------------------------	---------

#### Tripping

Short-time delayed tripping	No
-----------------------------	----

#### Endurance

Electric endurance in number of cycles	1000
Number of mechanical operations	7000

#### Installation, mounting

Tightening torque	3,5Nm
-------------------	-------

#### Connection

Connection cross-sect. flexible conductor	10 - 50 mm <sup>2</sup>
Connection cross-sect. rigid cable	10 / 70 mm <sup>2</sup>

#### Standards

Standard text	IEC 61009-1 ; EN 61009-1
---------------	--------------------------

