



EE180



IP20

Astronomical Time switch, 1 Channel

Technical characteristics

Functions

Function	Keylock by means of blocking key
----------	----------------------------------

Main electrical features

Frequency	50/60 Hz
-----------	----------

Electric current

Acceptable current rating with AC1	16 A
------------------------------------	------

Dimensions

Depth of installed product	65 mm
Height of installed product	85 mm
Width of installed product	65 mm

Power

Max. power with fluo uncompensated lamps	1000 VA
Power consumed	6 VA
Incandescent bulb power	0 / 2300 W
Total power loss under IN	2 W
Power dissipation per coil	0.3 W

Battery

Power reserve [years]	≈ 5 a
-----------------------	-------

Power supply

Supply voltage	230 V +/- 15%
----------------	---------------

Fluorescent bulbs control

Max. power with fluorescent parallel lamps	400 VA
Max. power fluo. duo lamp comp. series	1000 W

Incandescent bulbs control

Max. power with incandescent lamps	2300 W
------------------------------------	--------

Installation, mounting

Mounting type	din-Rail
---------------	----------

Connection

Connection cross-sect. flexible conductor	1 / 6mm ²
Connection cross-sect. rigid cable	1,5 / 10mm ²
Number of contacts	1

Type of contacts	1 changeover contact floating
------------------	-------------------------------

Settings

Summer / Winter time change	automatic
Shortest switching time	1 mn

Equipment

Number of channels	1
Supply failure reserve	5 years

Use

Cycle	weekly
-------	--------

Safety

Protection index IP	IP20
---------------------	------

Use conditions

Operating temperature	-10...55 °C
Working accuracy	1,5