



Digital time switch weekly 1 channel Evolution

Technical characteristics

| Rated operational voltage Ue | 195 / 230 / 264 V |
|------------------------------|-------------------|
| Frequency | 50 Hz |
| Dimensions | |
| Depth of installed product | 64 mm |
| Height of installed product | 85 mm |
| Width of installed product | 35 mm |
| Power | |
| Power consumed | 6 VA |
| Total power loss under IN | 2 W |
| Power dissipation per coil | 0.5 W |
| Battery | |
| Power reserve [years] | ≈ 5 a |
| | |

| Max. power with incandescent lamps | 2300 W |
|------------------------------------|--------|
| | |
| | |

| Connection | |
|--------------------|------------|
| Type of connection | with screw |
| Number of contacts | 1 |
| | |

| Type of connection | with screw terminals | |
|--------------------|----------------------|--|
| | | |

| automatic |
|-----------|
| 1 mn |
| digital |
| 1X7D. |
| |

| Equipment | | |
|------------------------|---------|--|
| Number of channels | 1 | |
| Supply failure reserve | 5 years | |
| Use | | |
| Cycle | weekly | |

| 5 years |
|---------|
| |
| |
| weekly |
| |
| IP20 |
| _ |

| se | conditions |
|----|------------|
| | comancioni |

| Operating temperature | -545 °C |
|-----------------------|---------|
| Working accuracy | 1 5 |