

2 x change-over contact

2X7D.









2 channels digital time switch weekly cycle

Technical characteristics

Functions	
Function	Keylock by means of blocking key
Configuration	

Main	electrical	features
------	------------	----------

Rated operational voltage Ue	195 / 230 / 265 V
Frequency	50 Hz

Dimensions

Switch mode

Depth of installed product	64 mm
Height of installed product	85 mm
Width of installed product	35 mm

Power

Power consumed	6 VA
Total power loss under IN	4 W
Power dissipation per coil	0.5 W

Battery

Power reserve [years]	≈ 5 a
Charging time of the power reserve in hours	0

Incandescent bulbs control

Max. power with incandescent lamps	2300 W
Max. power with incanaesterit lamps	2300 VV

Connection

Connection cross-sect. flexible conductor	1 / 16mm²
Connection cross-sect. rigid cable	1,5 / 10mm²
Number of contacts	2
Type of contacts	2 changeovers
Type of connection	with screw terminals

Settings

Summer / Winter time change	automatic
Shortest switching time	1 mn
Type of programming	digital

Equipment

Programming cycle

Number of channels	2
Supply failure reserve	5 years
Use	
Cycle	weekly
Use conditions	
Operating temperature	-545 °C
Working accuracy	1,5