

without



## Daily time switch 1 channel, 16A, 1 module

## **Technical characteristics**

| Configuration                             |                      |
|---|----------------------|
| Configuration Switch mode                 | NO contact           |
| Main electrical features                  |                      |
| Frequency                                 | 50 Hz                |
| rrequency                                 | 30 112               |
| Dimensions                                |                      |
| Depth of installed product                | 60 mm                |
| Height of installed product               | 80 mm                |
| Width of installed product                | 18 mm                |
| Power                                     |                      |
| Power consumed                            | 0.5 VA               |
| Power consumption (operation)             | 0.5 VA               |
| Total power loss under IN                 | 1 W                  |
| Power dissipation per coil                | 0.5 W                |
| Incandescent bulbs control                |                      |
| Max. power with incandescent lamps        | 900 W                |
| Installation, mounting                    |                      |
| Mounting type                             | din-Rail             |
| Connection                                |                      |
| Connection cross-sect. flexible conductor | 1 / 6mm²             |
| Connection cross-sect. rigid cable        | 1,5 / 10mm²          |
| Type of connection                        | with screw           |
| Number of contacts                        | 1                    |
| Type of contacts                          | 1 changeover         |
| Type of connection                        | with screw terminals |
| Settings                                  |                      |
| Summer / Winter time change               | manual               |
| Shortest switching time                   | 15 mn                |
| Type of programming                       | analog               |
| Programming cycle                         | 24H                  |
| Setting                                   | Setting via day dial |
| Equipment                                 |                      |
| Number of channels                        | 1                    |

Supply failure reserve

| Use                   |          |
|-----------------------|----------|
| Cycle                 | daily    |
| Use conditions        |          |
| Operating temperature | -1055 °C |
| Working accuracy      | 1        |