

50 Hz



EH110



## Daily time switch 1 channel, analog, 3 modules

## **Technical characteristics**

Frequency

Configuration	
Switch mode	change-over contact, usable as NC or NO
Main electrical features	

Dimensions	
Depth of installed product	54 mm
Height of installed product	90 mm
Width of installed product	65 mm

Power	
Power consumed	0.5 VA
Power consumption (operation)	0.5 VA
Total power loss under IN	1 W
Power dissipation per coil	0.5 W

Incandescent bulbs control	
Max. power with incandescent lamps	900 W

Installation, mounting	
Mounting type	din-Rail
Connection	
Connection cross sort flevible conductor	1 / 4mm²

Connection cross-sect. flexible conductor  Connection cross-sect. rigid cable  Type of connection  Number of contacts	1 / 4mm²
Type of connection	1 / 4mm²
<del></del>	2 /
Number of contacts	with screw
	1
Type of contacts	1 changeover
Type of connection with	n screw terminals

Summer / Winter time change	manual
Shortest switching time	15 mn
Type of programming	analog
Programming cycle	24H
Setting	Setting via day dial

Setting	Setting via day dial
Equipment	
Number of channels	1
Supply failure reserve	without

use	
Cycle	daily
Use conditions	
Operating temperature	-1045 °C
Working accuracy	1