



ERC218

Relay 16A, 1NO+1NC, 230V~50Hz

Technical characteristics

Main electrical features

| | |
|---------------------------------|-------|
| Rated operational voltage U_e | 230 V |
| Frequency | 50 Hz |

Voltage

| | |
|---------------------------------|-------|
| Rated insulation voltage | 250 V |
| Rated impulse withstand voltage | 4 kV |

Dimensions

| | |
|-----------------------------|----------|
| Depth of installed product | 60 mm |
| Height of installed product | 83 mm |
| Width of installed product | 17.85 mm |

Power

| | |
|----------------------------|-----|
| Total power loss under IN | 2 W |
| Power dissipation per coil | 1 W |

Endurance

| | |
|--|--------|
| Electric endurance in number of cycles | 30000 |
| Number of mechanical operations | 100000 |

Fluorescent bulbs control

| | |
|--|--------|
| Max. power with fluorescent parallel lamps | 490 VA |
|--|--------|

Incandescent bulbs control

| | |
|------------------------------------|--------|
| Max. power with incandescent lamps | 1100 W |
|------------------------------------|--------|

Equipment

| | |
|---------------------|-----|
| Can be accessorized | Yes |
|---------------------|-----|

Standards

| | |
|-------------------------|-----------|
| European directive WEEE | concerned |
|-------------------------|-----------|

Safety

| | |
|---------------------|------|
| Protection index IP | IP2X |
|---------------------|------|

Use conditions

| | |
|-----------------------|-------------|
| Operating temperature | -10...50 °C |
|-----------------------|-------------|