



Switch h1000 3P 1000A

Technical characteristics

| Neutral position | without neutral |
|---|-----------------------|
| Number of poles | 3 P |
| Type of pole | 3 P |
| Main electrical features | |
| Rated operational voltage Ue | 220 / 690 V |
| Frequency | 50/60 Hz |
| Voltage | |
| Rated insulation voltage | 800 V |
| Rated impulse withstand voltage | 8 kV |
| Power | |
| Total power loss under IN | 186 W |
| Endurance | |
| Electric endurance in number of cycles | 4500 |
| Number of mechanical operations | 15000 |
| Cover, door | |
| Interlockable | Yes |
| Connection | |
| Connection cross-sect. flexible conductor | 2x240mm ² |
| Connection cross-sect. rigid cable | 2x240mm ² |
| Type of connection | Terminal |
| Equipment | |
| Number of auxiliary contacts as normally | 0 |
| closed contact | |
| closed contact Number of auxiliary contacts as normally open contact | C |
| Number of auxiliary contacts as normally | |
| Number of auxiliary contacts as normally open contact Number of auxiliary contacts as change- | |
| Number of auxiliary contacts as normally open contact Number of auxiliary contacts as change- over contact | C |
| Number of auxiliary contacts as normally open contact Number of auxiliary contacts as change- over contact Standards | 0 0 IEC 60947-3 |