



HDA030E

**Moulded Case Circuit Breaker h3 x160 TM FIX 1P1D 32A 18kA CTC**

**Technical characteristics**

**Architecture**

Neutral position	without neutral
Number of poles	1 P

**Main electrical features**

Rated operational voltage Ue	220 / 240 V
Frequency	50/60 Hz
Type of supply voltage	AC

**Voltage**

Rated insulation voltage	690 V
Rated impulse withstand voltage	8 kV

**Dimensions**

Depth of installed product	68 mm
Height of installed product	130 mm
Width of installed product	25 mm

**Power**

Total power loss under IN	2.81 W
---------------------------	--------

**Endurance**

Electric endurance in number of cycles	1000
Number of mechanical operations	4000

**Installation, mounting**

Tightening torque	6Nm
-------------------	-----

**Connection**

Connection cross-sect. rigid cable	6 / 95mm <sup>2</sup>
------------------------------------	-----------------------

**Cable**

Cable Material	Cu
----------------	----

**Equipment**

Number of auxiliary contacts as normally closed contact	0
Number of auxiliary contacts as normally open contact	0
Number of auxiliary contacts as change-over contact	0
Can be accessorized	Yes

**Standards**

---

Standard text

IEC 60947-2

---

European directive WEEE

concerned