



HND631H

## Moulded Case Circuit Breaker h630 4P 50kA 630A LSI

### Technical characteristics

#### Electric current

Rated current	630 A
Rated ultimate short-circuit breaking capacity I <sub>cu</sub> under 230 V AC IEC 60947-2	85 kA
Rated ultimate short-circuit breaking capacity I <sub>cu</sub> under 240 V AC IEC 60947-2	85 kA
Rated ultimate short-circuit breaking capacity I <sub>cu</sub> under 400 V AC IEC 60947-2	50 kA
Rated ultimate short-circuit breaking capacity I <sub>cu</sub> under 415 V AC IEC 60947-2	50 kA
Breaking capacity on 1-pole for AC 230 V IEC 60947-2	51 kA
Breaking capacity on 1-pole for AC 400 V IEC 60947-2	9 kA

#### Architecture

Number of poles	4
Control/operation element	Toggle
Device construction type	Fixed built-in

#### Capacity

Number of modules	10.50
-------------------	-------

#### Tripping

Response time when opening	10 ms
----------------------------	-------

#### Settings

Magnetic protection knob setting xI <sub>N</sub>	2.5, 5, 8
Range of magnetic adjustment	3500 A, 4410 A, 5600 A, 6300 A, 6300 A, 6300 A, 6300 A, 6300 A
Thermal protection knob setting xI <sub>N</sub>	0.4, 0.5, 0.63, 0.8, 0.9, 0.95, 1
Adjustment range short-term delayed short-circuit release	0 - 0 A

#### Frequency

Frequency	50 - 60 Hz
-----------	------------

#### Installation, mounting

Nominal tightening torque	22 - 22 Nm
Mounting-/Connection Position	Front

#### Voltage

Rated impulse withstand voltage U <sub>imp</sub>	8,000 V
Rated insulation voltage U <sub>i</sub>	800 V

**Functions**

Trip unit	LSI
-----------	-----

**Main electrical attributes**

Magnetic protection trip time	100 - 200 ms
-------------------------------	--------------

**Power**

Total power loss under IN	120 W
Power loss per pole at In	40 W

**Endurance**

Electric endurance in number of cycles	1,000
Number of mechanical operations	4,000

**Equipment**

Number of auxiliary contacts as change-over contact	0
Number of auxiliary contacts as normally closed contact	0
Number of auxiliary contacts as normally open contact	0

**Safety**

Ingress Protection (IP) class	IP4X
-------------------------------	------

**Use conditions**

Operating temperature	-25 - 70 °C
-----------------------	-------------

**Connection**

Cross-section flexible conductor	35 - 240 mm <sup>2</sup>
Cross-section rigid conductor	35 - 240 mm <sup>2</sup>
Connector/plug type	Terminal

**Controls and indicators**

Motor drive integrated	No
------------------------	----

**Compatibility**

Suitable for DIN Rail	No
-----------------------	----

**Power supply**

Position power supply	Bidirectional
-----------------------	---------------