



NCN300A

## MCB 3P 10kA/15kA C-0.5A 3M

### Technical characteristics

#### Electric current

Rated current	0.50 A
Rated ultimate short-circuit breaking capacity Icu under 230 V AC IEC 60947-2	30 kA
Rated ultimate short-circuit breaking capacity Icu under 400 V AC IEC 60947-2	15 kA
Rated current -25°C	0.69 A
Rated current at -20°C	0.67 A
Rated current -15°C	0.66 A
Rated current -10°C	0.64 A
Rated current -5°C	0.63 A
Rated current at 0°C	0.61 A
Rated current 5°C	0.59 A
Rated current 10°C	0.58 A
Rated current 15°C	0.56 A
Rated current at 20°C	0.54 A
Rated current 25°C	0.52 A
Rated current 30°C	0.50 A
Rated current 35°C	0.48 A
Rated current at 40°C	0.45 A
Rated current at 45°C	0.43 A
Rated current at 50°C	0.40 A
Rated current 55°C	0.37 A
Rated current 60°C	0.34 A
Rated current 65°C	0.31 A
Rated current 70°C	0.27 A

#### Architecture

Type of pole	3P
Curve	C

#### Capacity

Number of modules	3
-------------------	---

#### Installation, mounting

Nominal tightening torque top terminal	2.80 - 2.80 Nm
Nominal tightening torque down terminal	2.80 - 2.80 Nm
Nominal tightening torque	2.80 - 2.80 Nm
Type of bottom connection for modular devices	biconnect

Type of top connection for modular devices	Screw terminal
360° mounting position possible	Yes
<b>Main electrical attributes</b>	
Rated short-circuit breaking capacity I <sub>cn</sub> AC according to IEC 60898-1	10 kA
<b>Voltage</b>	
Rated operational voltage U <sub>e</sub>	400 - 400 V
Type voltage supply	AC
Rated insulation voltage U <sub>i</sub>	500 V
Rated impulse withstand voltage U <sub>imp</sub>	6,000 V
<b>Frequency</b>	
Frequency	50 - 60 Hz
<b>Connection</b>	
Cross-section of input and output with screws, for massive conductors	1 - 35 mm <sup>2</sup>
Cross-section of input and output with screws, for flexible conductors	1 - 25 mm <sup>2</sup>
Cross-section of input with screws, for flexible conductors	1 - 25 mm <sup>2</sup>
Cross-section of input with screws, for massive conductors	1 - 35 mm <sup>2</sup>
<b>Safety</b>	
Ingress Protection (IP) class	IP20
<b>Use conditions</b>	
Degree of pollution according to IEC 60664 / IEC 60947-2	2
Class of energy limitation I <sup>2</sup> t	3
Operating temperature	-25 - 70 °C
<b>Power</b>	
Total power loss under I <sub>N</sub>	4.35 W
<b>Endurance</b>	
Electric endurance in number of cycles	4,000
Number of mechanical operations	20,000
<b>Connectivity</b>	
Type of connection	Screw terminal
Top connection alignment for modular devices	Aligned terminal
Down connection alignment for modular devices	Aligned terminal
<b>Dimensions</b>	
Height	83 mm
Width	52.50 mm
Depth	70 mm