



SB432PV

**Switch DC 4P 1000V 32A**

**Technical characteristics**

**Architecture**

Number of poles	4 P
Type of pole	4 P (1P ... +1P serie)

**Main electrical features**

Type of supply voltage	DC
------------------------	----

**Voltage**

Rated insulation voltage	1000 V
Rated impulse withstand voltage	8000 V

**Dimensions**

Depth of installed product	72 mm
Height of installed product	85 mm

**Power**

Total power loss under IN	6.9 W
---------------------------	-------

**Endurance**

Number of mechanical operations	10000
---------------------------------	-------

**Cover, door**

Interlockable	No
---------------	----

**Installation, mounting**

Tightening torque	1,8Nm
-------------------	-------

**Connection**

Connection cross-sect. flexible conductor	4 / 10mm <sup>2</sup>
Connection cross-sect. rigid cable	4 / 16mm <sup>2</sup>
Type of connection	with screw

**Equipment**

Number of auxiliary contacts as normally closed contact	0
Number of auxiliary contacts as normally open contact	0
Number of auxiliary contacts as change-over contact	0
Can be accessorized	No

**Standards**

Standard text	IEC 60947-3 ; VDE 0660
---------------	------------------------

**Use conditions**

---

Operating temperature

-40...65 °C