



TRE202



IP55

Module 2 outputs 10A IP55 KNX radio Quicklink

Technical characteristics

Architecture

| | |
|-------------|------------------|
| Bus system | KNX |
| Fixing mode | surface-mounting |

Controls and indicators

| | |
|----------------|-----|
| Indicator lamp | yes |
|----------------|-----|

Connectivity

| | |
|---------------------------|-----|
| Bus system radio frequent | Yes |
|---------------------------|-----|

Dimensions

| | |
|-----------------------|------------|
| Height | 35 mm |
| Width | 85 mm |
| Dimensions (LLxwwxhh) | 53 x 27 mm |

Materials

| | |
|--------------------|------|
| Surface appearance | matt |
|--------------------|------|

Fluorescent bulbs control

| | |
|--|-------|
| Max. power fluo. duo lamp comp. series | 600 W |
|--|-------|

Incandescent bulbs control

| | |
|------------------------------------|--------|
| Max. power with incandescent lamps | 1500 W |
|------------------------------------|--------|

Connection

| | |
|--------------------|------------------------------|
| Type of connection | with screw-in lift terminals |
|--------------------|------------------------------|

Use conditions

| | |
|-----------------------|-------------|
| Operating temperature | -10...55 °C |
|-----------------------|-------------|