



WMCS12



6A Ceiling Switch 2 Way

Technical characteristics

| lec | | | | |
|-----|--|--|--|--|
| | | | | |
| | | | | |

| Rated current | 6 A |
|---------------|-----|
| | |

Installation, mounting

| Mounting on | Flush mounting |
|-------------|----------------|
| | |

Voltage

| Rated voltage | 250 V |
|---------------|-------|
|---------------|-------|

Materials

| Colour | White | |
|----------------|-------------------|--|
| Surface finish | Glossy | |
| Material | Urea formaldehyde | |
| Treatment | Untreated | |

Identification

| Assembly arrangement | Basic element with full cover plate |
|----------------------|---------------------------------------|
| Assembly dirangement | Busic cicilient with full cover plate |

Connectivity

| Mounting type | Screw | mounting |
|---------------|-------|----------|
|---------------|-------|----------|

Controls and indicators

| Number of buttons | 0 |
|-------------------|---|
| | |

Dimensions

| Built-in depth | 0 |
|------------------|---|
| built-iii deptii | 0 |

Safety

| Ingress Protection (IP) class | IP20 |
|-------------------------------|------|
| ingress Protection (IP) class | 1120 |

Architecture

| Control/operation element | Pull cord |
|---------------------------|-----------|

Texts

| Lighting | Without lighting (cannot be illuminated) |
|-------------|--|
| Switch mode | 2-way |