



WMPS16



Intermediate Switch

Technical characteristics

| lectri | | |
|--------|--|--|
| | | |

| Switching current | 10 | |
|-------------------|------|--|
| Rated current | 10 A | |
| | | |

Installation, mounting

| Mounting on Flush mounting |
|----------------------------|
|----------------------------|

Voltage

| Rated voltage | 250 V |
|---------------|-------|
| | |

Materials

| Colour | Whi | |
|----------------|--------------------|--|
| Surface finish | Glossy | |
| Material | Polycarbonate (PC) | |
| Treatment | Untreated | |

Identification

| Assembly | arrangement | t Basic element with full | cover p | olate |
|----------|-------------|---------------------------|---------|-------|
| | | | | |

Connectivity

| Mounting type | Screw mounting |
|---------------|----------------|
|---------------|----------------|

Controls and indicators

| Number of buttons | 1 |
|-----------------------|---|
| realitibet of baccord | _ |

Dimensions

| Built-in depth | 13.10 mr | n |
|----------------|----------|---|
| | | |

Safety

| Ingress Protection (IP) class | IP20 |
|--------------------------------|-------|
| ingress rrotection (ii / class | 11 20 |

Architecture

Control/operation element Single rocker

Texts

| Lighting | Without lighting (cannot be illuminated) | |
|-------------|--|--|
| Switch mode | Intermediate | |